

TECHNICAL INFORMATION

Page: 1

PRODUCT	Natural Rubber (NR) Latex Male Condom						
DESCRIPTION	These condoms for men are made of natural rubber latex sheath, which completely covers the penis with a closely fitted membrane, and the condoms are reservoir ended, cornstarch powdered and silicone lubricated.						
INDICATION FOR USE	Contraceptive to prevent unintended pregnancy. Prevention of HIV infection (AIDS) and other sexually transmitted diseases (STDs).						
VARIANTS	Plain	Straight-Walled with Smooth Surface					
	Ultra Thin	Straight-Walled with Smooth Surface.					
	Super Dotted	Straight-Walled and Textured with Coarse Studs					
	Super Ribbed	Straight-Walled and Textured with Embossed Ribs					
	3 in 1	Contour-Walled with Partial Smooth Surface, Embossed Dots and Ribs					
	Anatomic	Contour-Walled with Smooth Surface					
	Luminant	Straight-Walled with Smooth Surface and Fluorescent Colour at Teat					
	G. Dotted	Straight-Walled and Partial Textured with Embossed Ribs & Dots.					
	Dual Dotted	Contour- Walled with Coarse Studs.					
MATERIALS	Ingredient Name			Function			
	Pre-Vulcanised NR Latex			Rubber Latex Sheath			
	Silicone Oil (Dimethyl Polysiloxane)			Lubricant			
	Modified Constarch Powder (USP grade)			Dusting Powder			
QUALITY CONTROL	The condoms are manufactured, tested and approved according to ISO 4074 and ASTM D3492 standards as well as WHO specification.						
	100% Electronically Tested			Hermetically Sealed(Package Integrity Tested)			
	On-Line quality control in all parts of manufacturing process.						
	Pre-Shipment quality control according to specified requirements.						
DIMENSIONS	Length	≥ 170 mm					
	Width	49 ± 2mm	51 ± 2mm	52 ± 2mm	53 ± 2mm	54 ± 2mm	56 ± 2mm
	Thickness	0.060 ± 0.015mm (Ultra Thin)	0.070 ± 0.015mm (Smooth)		0.075 ± 0.015mm (Textured)	≥ 0.080mm (Super Thick)	≥ 0.10mm (Super Strong)
PHYSICAL PROPERTIES	Pin Holes	AQL 0.25, General Inspection Level 1					
	Tensile (Unaged)	Force at Break	≥ 100N (Super Strong)				
		Elongation at Break	≥ 700% (Super Strong)				
	Bursting (Unaged & Aged)	AQL 1.5, General Inspection Level 1					
		Pressure	≥ 1.0 kPa (Normal), ≥ 2.0 kPa (Extra Strong)				
		Volume	≥ 16.0 kPa (49mm), ≥ 18.0 kPa (53mm), ≥ 22 kPa (56mm)				
PACKAGING	Each condom is packed in approx. 55x55(49/53mm condom)/59x57mm(56mm condom) square or or (29x69)mm for rectangular aluminium foil.						
	3 pieces in wallet pack or box pack or 12 pieces in box pack or bulk pack.						

TECHNICAL INFORMATION

Page: 2

STORAGE	Store in a cool, dry place away from direct sunlight.
SHELF-LIFE	5 years
CE MARK	Annex 2, Class 2b
QUALITY SYSTEM & PRODUCT MARKINGS	ISO 9001, ISO 13485, NF Mark (France), SABS Mark (South Africa), SIRIM Mark (Malaysia), CCC Mark (China), US FDA 510(k) Approval, China SFDA Approval, Russia MOH.
ORIGIN	Made in Malaysia
MANUFACTURER NAME	PLEASURE LATEX PRODUCTS SDN. BHD.
MANUFACTURER ADDRESS	Lot 5322, 15th Miles, Jalan Padang Gajah 45800, Jeram, Selangor Darul Ehsan, Malaysia.
TELEPHONE	603 - 3250 0377
FACIMILE	603 - 3250 3069
E-MAIL	qa@plplatex.com
WEBSITE	www.plp.com.my

Note : This technical data/information is subject to change without notice.

Yours truly,
PLEASURE LATEX PRODUCTS SDN. BHD.
Irene Ting
QUALITY ASSURANCE MANAGER / ASST.
E-Mail: qa@plplatex.com